

DH Series Double Headed Ties

Features and Benefits

Designed with two heads, these ties can be assembled into a 'figure 8' for securing two cables. Its flexible adjustment means that the bundles can be of different sizes.

Application

Ideal for running two cables in parallel, that need to be separated. These ties allow for installation of a second cable run without the need for additional cable ties.

The DH ties are also widely used within the packaging industry - the first loop closes and secures the bag, whilst the second loop can be made into a carrying handle (subject to weight).



Bundling two cable runs using the DH ties.



DH Series

Material Data

RoHS	Material	Polyamide 6.6 (PA66)	HF (halogenfree)
	Operating Temperature	-40°C to +85°C Continuous, (+105°C for 500 h)	
	Flammability	UL94 V2	

Material Data

RoHS	Material	Polyamide 4.6 (PA46)	HF (halogenfree)
	Operating Temperature	-40°C to +150°C for 5000 h, (+195°C for 500 h)	
	Flammability	UL94 V2	

Material Data

RoHS	Material	Polyamide 6.6 UV Resistant (PA66W)	HF (halogenfree)
	Operating Temperature	-40°C to +85°C Continuous, (+105°C for 500 h)	
	Flammability	UL94 V2	

Material Data

RoHS	Material	Polyamide 6.6 Heat Stabilised (PA66HS)	HF (halogenfree)
	Operating Temperature	-40°C to +105°C Continuous, (+145°C for 500 h)	
	Flammability	UL94 V2	

Technical Table

Code	Length (L)	Width (W)	Ø per loop max.	Min. Tensile Strength (N)	Min. Tensile Strength (N) 2nd Loop	Material	Colour	Application Tool
T50RDH	210	4.7	50	225	180	PA66	Black (BK)	1-10
T50RDH	210	4.7	50	225	180	PA66	Natural (NT)	1-10
T50RDH	210	4.7	50	225	180	PA66W	Black (BK)	1-10
T50RDH	210	4.7	50	225	180	PA66HS	Black (BK)	1-10
T50RDH	210	4.7	50	225	180	PA46	Grey (GY)	1-10
T50IDH	305	4.7	38	225	180	PA66	Black (BK)	1-10
T50IDH	305	4.7	38	225	180	PA66	Natural (NT)	1-10
T50IDH	305	4.7	38	225	180	PA66W	Black (BK)	1-10
T50LDH	395	4.7	50	225	180	PA66	Black (BK)	1-10
T50LDH	395	4.7	50	225	180	PA66	Natural (NT)	1-10
T50LDH	395	4.7	110	225	180	PA66W	Black (BK)	1-10
T50LDH	395	4.7	110	225	180	PA66HS	Black (BK)	1-10

All dimensions in mm. Subject to technical changes.



Please Note for Product Specific Approvals please refer to Appendix.