


## Automatic Harness Clips

### Features and Benefits

These clips can be attached to the panel prior to installing the cables, simply pushing the cable into place, closes the clip which activates the automatic locking feature. The parts prefixed with an 'I' can be interlocked giving a greater choice of installation options.

### Application

Offering a simple and secure method of attaching cables to panels. Originally designed for the automotive industry they are finding a wide variety of applications in all industries using sheet metal panels.



AHC 1AH - 2AH



AHC2 SS


Technical Table											
Code	Length (L)	Length (L2)	Width (W)	Disc Ø	Bundle Ø max.	Fixing Hole Ø (FH)	Panel Thickness min.	Panel Thickness max.	Material Shortcut	Colour	
AHC1AH	25.0	7.0	10.0	20.0	13.0	6.2-6.7	0.5	2.0	PA66	Black (BK)	
AHC2AH	29.5	7.0	10.0	20.0	20.0	6.2-6.7	0.5	2.0	PA66	Black (BK)	
AHC2SS	31.5	-	10.0	-	20.0	-	-	-	PA66	Black (BK)	
<b>Connectable</b>											
IAHC3AH	39.0	7.0	10.0	24.0	28.0	6.2-6.7	0.5	2.7	PA66	Black (BK)	
IAHC4AH	46.0	7.0	13.0	24.0	36.0	6.2-6.7	0.5	2.5	PA66	Black (BK)	
IAHC1T	23.0	-	10.0	-	13.0	-	-	-	PA66	Black (BK)	
IAHC2T	30.0	-	10.0	-	20.0	-	-	-	PA66	Black (BK)	
IAHC3T	40.0	-	10.0	-	28.0	-	-	-	PA66	Black (BK)	
IAHC4T	47.0	-	13.5	-	36.0	-	-	-	PA66	Black (BK)	
IAHC5T	57.0	-	13.5	-	45.0	-	-	-	PA66	Black (BK)	

All dimensions in mm. Subject to technical changes.

Material Data	
Material	Polyamide 6.6 (PA66)
Colour	Black (BK)
Operating Temperature	-40°C to +85°C Continuous, (+105°C for 500 h)
Flammability	UL94 V2

RoHS

HF  
(halogenfree)



AH



T



Elements AH and T connected