

### T609 200A AC

- Jaw size 19mm
- Pocket-size
- Data hold
- Auto power off
- Maximum current hold



Technical Specification	
AC Current	2A,20A,200A
Accuracy	
AC Current	0 - 2,4 0,001A 0 - 2,4 0,001A 0 - 2,4 0,001A
Frequency	50Hz - 60Hz

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	155(L) x 50(W) x 25(H)
Power Source	2 x 1,5V Battery LR44 (T515BATT)
Weight	95g

### TBM3030 600A AC

- Jaw size 26mm
- Large LCD display
- Diode
- Continuity
- Relative zero
- Data hold
- Thinner jaws



Technical Specification	
AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	5Hz to 100KHz
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC Current	±1,9%+ 8 Digit
DC Voltage	±1,0%+ 4 Digit
AC Voltage	4,40,400V ±1,5%+ 5 Digit 600V ±2,0%+ 5 Digit
Resistance	4K,40K,400KΩ ± 0,6%+4 Digit 4MΩ ± 1,0%+ 4 Digit 40MΩ ± 2,0%+ 4 Digit
Frequency	± 0,5%+ 4 Digit
Capacitance	± 3,5%+ 6 Digit
Protection	
AC/DC Voltage	600V DC/AC RMS
Current	400A RMS CONTINUOUS
Transient	6.5KV LIGHTNING SURGE (1.2/50 μs)

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	190(L) x 63(W) x 32(H)
Power Source	3V CR2032 (TBMBATT)
Weight	187g

### TBM126 600A AC Dual Display

- Jaw size 26mm
- Temperature
- Diode
- Continuity
- Relative zero
- Data hold
- Thinner jaws



Technical Specification	
AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	5Hz to 100KHz
Temperature	-20°C to 300°C
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC Current	±1,9%+ 8 Digit
DC Voltage	±1,0%+ 4 Digit
AC Voltage	4,40,400V ± 1,5%+ 5 Digit 600V ± 2,0%+ 5 Digit
Resistance	4K,40K,400KΩ ± 0,6%+4 Digit 4mΩ ± 1,0%+ 4 Digit 40mΩ ± 2,0%+ 4 Digit
Frequency	±0,5%+ 4 Digit
Temperature	±2,0 % + 3°C
Capacitance	±3,5%+ 6 Digit
Protection	
AC/DC Voltage	600V DC/AC RMS
Current	400A RMS CONTINUOUS
Transient	6.5KV Lightning Surge
Protection	(1.2/50 μs)

Model Specification	
Accessories	Carry Pouch, Temp Probe
Dimensions (mm)	190(L) x 63(W) x 32(H)
Power Source	2 x 3V CR2032 (TBMBATT)
Weight	187g

### T2600 200A AC Open Jaw Clamp

- Open jaw 12mm
- Backlight
- Duty cycle
- Capacitance
- Frequency
- Diode
- Continuity
- Relative zero
- Data hold



Technical Specification	
AC Current	200A
DC Voltage	4,40,400,1000v
AC Voltage	4,40,400,700v
Resistance	400,4k,40k,400k,4m,40m
Frequency	40,400,4k,40k,100khz
Capacitance	40n,400n,4μ,40μf
Accuracy	
AC Current	±3,0%+ 3 Digit
DC Voltage	±0,8%+ 3 Digit
AC Voltage	±1,0%+ 10 Digit
Resistance	±2,0%+ 3 Digit
Frequency	±2,0%+ 1 Digit
Capacitance	±4,0%+ 10 Digit

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	192(L) x 68(W) x 43(H)
Power Source	9V Battery
Weight	230g

### T98 1000A AC

- Jaw size 42mm
- Backlight
- Continuity
- Data hold



#### Technical Specification

AC Current	20,200,1000A
DC Voltage	1000V
AC Voltage	750V
Resistance	200,2000Ω
Temperature	-40°C to 750°C
<b>Accuracy</b>	
AC Current	±2,0% + 5 Digit
DC Voltage	±1,0% + 2 Digit
AC Voltage	±1,0% + 5 Digit
Resistance	±1,0% + 3 Digit
Temperature	±1,0% + 5 Digit

#### Model Specification

Accessories	Carry Pouch, Temp Probe
Dimensions (mm)	250(L) x 99(W) x 43(H)
Power Source	9V Battery
Weight	460g

### T260D 1000A AC Combination Clamp

- Jaw size 60mm
- Diode
- Continuity buzzer
- Plug-in insulation tester adaptor 500 V DC (Optional) T261

#### Technical Specification

AC Current	20,200,1000A
AC Voltage	200,750V
DC Voltage	200m,20,200,1000V
Resistance	200,2K,20K,200K,2MΩ
<b>Accuracy</b>	
DC Voltage	±0,5% + 1 Digit
AC Voltage	±1,2% + 10 Digit
AC Current	±2% + 5 Digit
Resistance	±1,0% + 2 Digit
<b>Protection</b>	
DC Voltage	1200V DC/ 850 V AC
AC Voltage	1200V DC/ 850 V AC
AC Current	1200A for 60 sec
Resistance	500V AC/DC

#### Model Specification

Dimensions (mm)	230(L) x 70(W) x 37(H)
Power Source	9V Battery
Weight	310g



### T261 Plug-in Insulation Tester

#### Technical Specification

Ranges	20MΩ, 2000MΩ
<b>Accuracy</b>	
20MΩ	2% rdng + 2 Digit
2000MΩ	4% rdng + 2 Digit
Rated Voltage	500V DC

#### Model Specification

Dimensions (mm)	90(L) x 70(W)
Power Source	4 x 1.5V AA Batteries
Weight	500g



### T2312 1000A AC

- Jaw Size 40mm
- Back Light and Clamp Light
- Data Hold
- Resistance
- Frequency
- Overmould
- Capacitance
- Diode

#### Technical Specification

AC Current	1,600,1000A
AC Voltage	6,60,600,700V
DC Voltage	6,60,600,1000V
Resistance	600,6K,60K,600K,6M,60MΩ
Frequency	40,600,6K,60K,100KHz
Capacitance	600n,6μ,60μ,600μ,1000μF
<b>ACCURACY</b>	
AC/DC Current	± 3 % + 5 Digit
AC/DC Voltage	± 1.2 % + 5 Digit
Resistance	± 1 % + 3 Digit
Frequency	± 0.1 % + 1 Digit
Capacitance	± 4 % + 5 Digit
<b>PROTECTION</b>	
AC Current	120% Ranges for 60 sec
AC/DC Voltage	1000V DC or 700V AC rms
Resistance	250V DC rms AC for all ranges
Frequency	1V to 10V rms 40Hz to 100KHz
Capacitance	250V DC or rms AC for all ranges

#### Model Specification

Accessories	Carry Pouch
Dimensions (mm)	225(L) x 86(W) x 32(H)
Power Source	3 x 1.5V AAA Batteries
Weight	320g



### T2026 1000A AC



- Jaw Size 40mm
- Back Light and Clamp Light
- Data Hold
- Resistance
- Frequency
- Overmould
- Diode
- Capacitance

#### Technical Specification

AC Current	1,600,1000A
AC Voltage	6,60,600,700V
DC Voltage	6,60,0600,1000V
Resistance	600,6K,60K,600K,6M,60MΩ
Frequency	40,600,6K,60K,100KHz
Capacitance	600n,6μ,60μ,600μ,1000μF
<b>ACCURACY</b>	
AC/DC Current	± 3 % + 5 Digit
AC/DC Voltage	± 1.2 % + 5 Digit
Resistance	± 1 % + 3 Digit
Frequency	± 0.1 % + 1 Digit
Capacitance	± 4 % + 5 Digit
<b>PROTECTION</b>	
AC Current	120% ranges for 60 sec
AC/DC Voltage	1000V DC or 700V AC rms
Resistance	250V DC rms AC for all ranges
Frequency	1V to 10V rms 40Hz to 100KHz
Capacitance	250V DC or rms AC for all ranges

#### Model Specification

Accessories	Carry Pouch
Dimensions (mm)	225(L) x 86(W) x 32(H)
Power Source	3 x 1.5V AAA Batteries
Weight	320g



Digital Clamp Meters

**TBM116 1000A AC Auto Check**

True RMS

- Jaw size 45mm
- Diode
- Continuity
- Relative zero
- Data hold

CAT III 600V IEC61010-1

LISTED UL



Meter Supplied With Certificate of Conformance

Technical Specification

AC Current	400,1000A
DC Voltage	400m,4,40,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,40MΩ
Accuracy	
DC Voltage	2% + 4 Digit
AC Voltage	3% + 5 Digit
AC Current	1,5% + 5 Digit
Resistance	1,2% + 4 Digit
Protection	
AC Current	600A AC Continuous
AC/DC Voltage	600V DC/AC Rms
Transient	6KV Lightning Surge (1.2/50 μs)
Protection	

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	220g

**TBM118 2000A AC Autocheck**

True RMS

- Jaw size 45mm
- Emf detection
- Diode
- Continuity
- Relative zero
- Data hold

CAT III 600V IEC61010-1

LISTED UL



Meter Supplied With Certificate of Conformance

Technical Specification

AC Current	400,2000A
DC Voltage	6,60,600V
AC Voltage	6,60,600V
Resistance	6K,60K,600K,6MΩ
Frequency	10 to 50KHz
Capacitance	100n,1000n,10μ,100μ,2000μF
Accuracy	
DC Voltage	2% + 5 Digit
AC Voltage	1,5% + 5 Digit
AC Current	1,5% + 5 Digit
Resistance	1,2% + 4 Digit
Frequency	0,5% + 4 Digit
Capacitance	3,5% + 5 Digit
Protection	
AC Current	2000A AC Continuous
AC/DC Voltage	600V DC/AC Rms
Transient	6KV Lightning Surge (1.2/50 μs)
Protection	

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	220g

**TBM135 1000A AC Data Logger**

True RMS

- Jaw Size 45mm
- Backlight
- 5400 Point Logging
- Record Function
- Continuity

CAT III 600V IEC61010-1

LISTED UL



Meter Supplied With Certificate of Conformance

Technical Specification

AC Current	40,400,1000A
DC Voltage	600V
AC Voltage	600V
Resistance	999,9Ω
Frequency	5 to 500Hz
Temperature	-50 to 300°C
Thd%-r	0,0%~99,9%
Accuracy	
DC Voltage	0,5% + 5 Digit
AC Voltage	1,5% + 5 Digit
AC Current	2,0% + 5 Digit
Resistance	1,0% + 6 Digit
Frequency	0,5% + 4 Digit
Temperature	2% + 3°C
Thd%-r	Fundamental 1% + 6 Digit 2~3 Harmonics 5% + 6 Digit 4~51 St Harmonics 2%
Protection	
AC Current	1000A AC rms Continuous
AC/DC Voltage	600V DC/AC rms
Transient	6KV Lightning Surge (1.2/50 μs)
Protection	

Model Specification

Optional Accessories	RS232 Cable & Software (TBR13X) See PG 6 for USB Adaptor
Accessories	Carry Pouch, Type-K Thermocouple
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	224g

**T223 100A AC/DC Automotive**

- Jaw size 12.5mm
- Concurrent Reading
- Resistance
- Continuity



Technical Specification

AC/DC Current	1mA,10mA,10A,100A
AC/DC Voltage	0,1V, 600V
Resistance	1, 10kΩ
Accuracy	
AC/DC Current	± 2 % + 10 Digit
AC/DC Voltage	± 1,5 % + 5 Digit
Resistance	± 1 % + 3 Digit
Protection	
AC/DC Voltage	660Vrms
AC/DC Current	150A Rms

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	202(L) x 70(W) x 34(H)
Power Source	2 x 1.5V AA Batteries
Weight	180g

### TCM02 200A AC/DC

- Jaw Size 23mm
- Auto zero adjustment
- Data hold
- Diode
- Continuity
- Temperature
- Capacitance
- Bar Graph



#### Technical Specification

DC/AC Current	40,200A
DC/AC Voltage	4,40,400,600V
Resistance	400,4K,40K,4MΩ,40MΩ
Frequency	100KHz
Temperature	-40°C to 1000°C
Capacitance	4n,40n,400n,4μ,40μF
<b>Accuracy</b>	
AC/DC Current	±1.5% ± 2 Digit
AC/DC Voltage	±1.5% ± 3 Digit
Resistance	±1.5% ± 2 Digit
Frequency	±0.5% ± 2 digits
<b>Protection</b>	
AC/DC Current	400A AC/DC
DC Voltage	800V DC
AC Voltage	800V AC
Other Ranges	600V AC

#### Model Specification

Dimensions (mm)	183(L) x 64(W) x 36(H)
Power Source	2x 1.5V AAA Battery
Weight	190g

### T2102 400A AC/DC

- Jaw Size 28mm
- Diode
- Continuity
- Data hold
- Zero mode
- Auto power off
- Bar Graph



#### Technical Specification

DC/AC Current	40,400A
DC/AC Voltage	1,400,600V
Resistance	400,4K,40K,200K,2.4MΩ
<b>Accuracy</b>	
AC/DC Current	±2.5% ± 5 Digit
AC/DC Voltage	±1.0% ± 5 Digit
Resistance	±1.0% ± 5 Digit
<b>Protection</b>	
AC/DC Current	500V AC/DC
DC Voltage	600V DC
AC Voltage	600V AC
Other Ranges	600V AC

#### Model Specification

Dimensions (mm)	194(L) x 72(W) x 35(H)
Power Source	2x 1.5V AAA Battery
Weight	210g

### T8056 1000A AC/DC

- Jaw Size 42mm
- Duty Cycle
- Diode
- Continuity
- Auto Power Off
- Relative Zero
- Data Hold



#### Technical Specification

DC/AC Current	400,1000A
DC Voltage	400m,4,40,400,1000V
AC Voltage	4,40,400,700V
Resistance	400,4K,40K,400K,4m,40MΩ
Frequency	40,400,4k,40k,100KHz
Temperature	-40°C to 750°C
Capacitance	4n,40n,400n,4μ,40μF
<b>Accuracy</b>	
DC Current	±3,0% ± 3 Digit
AC Current	±3,0% ± 3 Digit
DC Voltage	±0,8% ± 3 Digit
AC Voltage	±1,0% ± 10 Digit
Resistance	±2,0% ± 3 Digit
Frequency	±2,0% ± 1 Digit
Temperature	±1,0% ± 6 Digit
Capacitance	±4,0% ± 10 Digit
<b>Protection</b>	
AC/DC Voltage	1000V DC or 700V AC RMS
AC/DC Current	120% For 60 Seconds

#### Model Specification

Accessories	Carry Case & Temp Probe
Dimensions (mm)	250(L) x 99(W) x 43(H)
Power Source	9V Battery
Weight	480g

### T2138 1000A AC/DC

- Jaw Size 40mm
- Back Light and Clamp Light
- Data Hold
- Resistance
- Frequency
- Overmould
- Diode

#### Technical Specification

AC/DC Current	1,400,600,1000A
AC Voltage	4,40,400,600,700V
DC Voltage	4,40,400,600,1000V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	40,400,4k,40k,100KHz
<b>Accuracy</b>	
AC/DC Current	± 3 % ± 5 Digit
AC/DC Voltage	± 0.8 % ± 5 Digit
Resistance	± 1 % ± 5 Digit
Frequency	± 0.1 % ± 1 Digit
<b>Protection</b>	
AC/DC Current	120% Ranges for 60 Sec
AC/DC Voltage	1000V DC or 700V AC RMS
Resistance	250V DC RMS AC for all ranges
Frequency	1V to 10V RMS 40Hz to 100KHz

#### Model Specification

Accessories	Carry Pouch
Dimensions (mm)	225(L) x 86(W) x 32(H)
Power Source	3 x 1.5V AAA Batteries
Weight	320g



Digital Clamp Meters

T2606 1000A AC/DC



- Jaw Size 40mm
- Back Light and Clamp Light
- Data Hold
- Resistance
- Frequency
- Overmould
- Diode



Technical Specification	
AC/DC Current	1,400,600,1000A
AC Voltage	4,40,400,600,700V
DC Voltage	4,40,400,600,1000V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	40,400,4K,40K,100KHz
Accuracy	
AC/DC Current	± 3 % + 5 Digit
AC/DC Voltage	± 0.8 % + 5 Digit
Resistance	± 1 % + 5 Digit
Frequency	± 0.1 % + 1 Digit
Protection	
AC/DC Current	120% ranges for 60 sec
AC/DC Voltage	1000V DC or 700V AC RMS
Resistance	250V DC RMS AC for all ranges
Frequency	1V to 10V RMS 40Hz to 100KHz

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	225(L) x 86(W) x 32(H)
Power Source	3 x 1.5V AAA Batteries
Weight	320g

TBM162 1000A AC/DC



- Jaw Size 50mm
- Large display
- Max hold
- Continuity
- Diode
- Back light



Technical Specification	
AC/DC Current	1,400,800,1000A
AC Voltage	600V
DC Voltage	600V
Resistance	400,4K,4M,40MΩ
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC/DC Current	± 2 % + 5 Digit
AC Voltage	± 1.5 % + 4 Digit
DC Voltage	± 0.5 % + 3 Digit
Resistance	± 1.0 % + 4 Digit
Capacitance	± 3.5 % + 6 Digit
Protection	
AC/DC Current	DC 1000A or 800A RMS
Transient	6.5kV LIGHTNING SURGE
Protection	(1.2 / 50μs surge)



Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	227(L) x 78(W) x 40(H)
Power Source	2 x 1.5V AAA Batteries
Weight	290g

T2608 2000A AC/DC



- Jaw Size 57mm
- Min/Max
- Data hold
- Peak hold
- Bargraph
- Auto Power OFF
- Diode
- Continuity



Technical Specification	
DC/AC Current	400,2000A
AC Voltage	400m,4,40,400,750V
DC Voltage	400m,4,40,400,1000V
Resistance	400,4k,40k,400k,4m, 40MΩ
Capacitance	4n,40n,400n,4μ,40μF
Frequency	10,1K,10K,100K,400KHz
Accuracy	
AC/DC Current	±1.5% rdg + 5 Digit
AC Voltage	±1.5% rdg + 4 Digit
DC Voltage	±0.5% rdg + 1 Digit
Resistance	±1.0% rdg + 4 Digit
Frequency	±0.1% rdg + 4 Digit
Capacitance	±1.0% rdg + 4 Digit
Protection	
AC/DC Current	2000A for 60 sec
AC/DC Voltage	1000V DC/750V RMS
Other Ranges	500V DC/AC RMS



Model Specification	
Dimensions (mm)	277(L) x 102(W) x 49(H)
Power Source	9V Battery
Weight	540g

TBM157 1000A 3 PHASE POWER



- Jaw Size 45 mm
- Total Power Factor
- THD%-F (Total harmonic distortion)
- Peak Hold
- RS232
- 3 Phase unbalanced load
- Back light



Technical Specification	
AC Current	40,400,1000A
DC Voltage	600V
AC Voltage	600V
Resistance	999,9Ω
Frequency	5 ~ 500Hz
Thd%-f	0,0% ~ 999,9%
Power	0,00 ~ 600kVA 0,00 ~ 600kW 0,00 ~ 600kVAR
Accuracy	
DC Voltage	0,5% + 5 Digit
AC Voltage	1,5% + 5 Digit
AC Current	2,2% + 5 Digit
Resistance	1,0% + 6 Digit
Frequency	0,5% + 4 Digit
Thd%-f	Fundamental 1,5%+6 Digit 2-3 Harmonics 7%+6 Digit 4-51 Harmonics 2%+6 Digit
Power Kva	0,99-0,01 F-10th 2,0%+6 Digit 11-50th 3,5%+6 Digit 51th 4,5%+6 Digit
Power Kw +Kvar Range	PF 0,99-0,70 F-10th 2,0%+6 Digit 11-50th 3,5%+6 Digit 51th 5,5%+6 Digit PF 0,70-0,50 F-10th 3,0%+6 Digit 11-50th 3,5%+6 Digit 51th 5,5%+6 Digit PF 0,50-0,30 F-10th 3,5%+6 Digit 11-50th 3,5%+6 Digit 51th 5,5%+6 Digit PF 0,30-0,01 F-10th 10%+6 Digit 11-50th 10%+6 Digit 51th 12%+6 Digit
Power Factor	0,01 ~ 0,99 F-21st 3 Digits 22-51st 5 Digits
Protection	
AC Current transient protection	1000A RMS CONTINUOUS 6KV LIGHTNING SURGE (1,2/50 μs)



Model Specification	
Optional Accessories	RS232 Cable & Software (TBR13X) See PG 6 for USB Adaptor
Accessories	Carry Pouch
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	224g



### TCM03 AC Earth Leakage

- Jaw Size 30mm
- Data hold
- Auto power off
- Continuity
- Zero/Relative Button



#### Technical Specification

AC Current	40m,400m,4,40,60A
AC Voltage	400V
Resistance	400Ω
<b>Accuracy</b>	
AC Current	±1,0% rdg + 3 Digit
AC Voltage	±1,5% rdg + 2 Digit
Resistance	±1,0% rdg + 2 Digit
Overload	600V RMS
Protection	

#### Model Specification

Dimensions (mm)	210(L) x 62(W) x 36(H)
Power Source	2 x 1.5V AA Batteries
Weight	200g

### TE1602

- Optional accessories for T2016 (Telecoms) Earth spike kit



<b>Wire Lengths:</b>	<b>Accessories:</b>
4 x 1 meters	Cable on reels
4 x 30 meters	4 Earth Spikes
	Hammer
	Carry Case

### TA300 300A AC

- Jaw Size 34mm
- Low cost
- Resistance
- Frequency 50Hz/60Hz



#### Technical Specification

AC Current	6,15,60,150,300A
AC Voltage	150,300,600V
DC Voltage	75V
Resistance	0-2KΩ, 0-200KΩ
<b>Accuracy</b>	
AC Current	±3% of full scale
AC Voltage	±3% of full scale
DC Voltage	±3% of full scale
Resistance	±3% of scale length
Overload	0,5 A/250 V
Protection	

#### Model Specification

Dimensions (mm)	195(L) x 80(W) x 36(H)
Power Source	1.5V AA Batteries
Weight	350g

### T500T 600A AC

- Jaw Size 34mm
- Resistance
- Temperature



#### Technical Specification

AC Current	6,15,60,150,600A
AC Voltage	150,300,750V
DC Voltage	75V
Resistance	50,2K,200K
Temperature	-20°C - 150°C
<b>Accuracy</b>	
AC Current	±3% of full scale
AC Voltage	±3% of full scale
DC Voltage	±3% of full scale
Resistance	±3% of full scale
Temperature	±3% of full scale
Overload	0,5 A/250 V
Protection	

#### Model Specification

Accessories	Temp probe
Dimensions (mm)	214(L) x 85(W) x 43(H)
Power Source	1.5V AA Battery
Weight	350g

### T1000 1000A AC

- Jaw Size 52mm
- Rotary scale
- Pointer lock
- Tear drop jaws
- Frequency 50Hz/60Hz



#### Technical Specification

AC Current	10,30,100,300,1000A
AC Voltage	150,300,750V
Resistance	0-2KΩ
<b>Accuracy</b>	
AC Current	±3% of full scale
AC Voltage	±3% of full scale
Resistance	±3% of scale length
Clamp	2500V AC for 1 minute
Withstand Voltage	

#### Model Specification

Dimensions (mm)	227(L) x 73(W) x 33(H)
Power Source	None
Weight	460g